

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

1 Identification of the substance/mixture and of the company/undertaking

Product identifier
Trade name: Interior-Wax

Article number: 7393, 7394

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture
Coating compound/ Surface coating/ paint
Paint

Details of the supplier of the safety data sheet
Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany

Further information obtainable from:
Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

Emergency telephone number:

 emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English
 Members of the public seeking specific information on poisons should contact:
 In England and Wales: NHS 111 - dial 111
 In Scotland: NHS 24 - dial 111
 IE: National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)
 Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

Importer

 Importer for UK:
 OSMO UK,
 Smeaton Close
 Unit 24 Anglo Business Park
 Aylesbury, Bucks HP19 8UP
 Phone: 01296 481 220, www.osmouk.com
 United Kingdom

2 Hazards identification

Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Label elements
Hazard pictograms

Void

(Contd. on page 2)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 1)

Signal word	Void
Hazard statements	Void
Precautionary statements	P102 Keep out of reach of children.
Additional information:	EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
Other hazards	Always wear a dust mask when sanding. Observe the general safety regulations when handling chemicals.
Results of PBT and vPvB assessment	
PBT:	Not applicable
vPvB:	Not applicable

3 Composition/information on ingredients

Chemical characterisation: Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 2634-33-5 Reg.nr.: 01-2120761540-60	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036 %	<0.02%
CAS: 55965-84-9 EINECS: 220-239-6	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.0015%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures

General information:	Take affected persons out into the fresh air. Immediately remove any clothing soiled by the product.
After inhalation:	In case of unconsciousness place patient stably in side position for transportation.
After skin contact:	Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor. If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 3)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 2)

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

Information for doctor:
Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

Extinguishing media
Suitable extinguishing
agents: Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable
extinguishing agents: None known.

Special hazards arising from
the substance or mixture No further relevant information available.

Advice for firefighters
Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for
containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Ensure adequate ventilation.

Warm water and cleansing agent

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 3)

7 Handling and storage

Handling:

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Avoid contact with skin and eyes.

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection:

The product is not flammable.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required

Further information about

storage conditions: Protect from frost.

Storage class: TRGS 510 storage class: 12 non-flammable liquids that can not be assigned to any other storage class.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs**CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one**

Dermal	DNEL Arbeitnehmer (Langzeit - systemische Effekte)	0.966 mg/kgKG/Tag
	DNEL Verbraucher (Langzeit - systemische Effekte)	0.345 mg/cm ²
Inhalative	Worker (chronic - Systemic health effec)	6.81 mg/m ³

(Contd. on page 5)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 4)

	DNEL Verbraucher (Lanzzeit - systemische Effekte)	1.2 mg/m ³
CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		
Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	0.09 mg/kgKG/Tag
	DNEL Verbraucher (AKUT - systemische Effekte)	0.11 mg/kgKG/Tag
Inhalative	DNEL Arbeitnehmer (Langzeit - lokale Effekte)	0.02 mg/m ³
	DNEL Verbraucher (Langzeit - lokale Effekte)	0.02 mg/m ³

PNECs

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

PNEC sea water	0.00339 mg/l
PNEC fresh water	0.0039 mg/l
PNEC sediment (fresh water)	0.027 mg/kg
PNEC sediment (sea water)	0.027 mg/kg
PNEC soil	0.01 mg/kg

Additional information: The lists valid during the making were used as basis.

Exposure controls**Personal protective equipment:**
**General protective and
hygienic measures:**

Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Only during spraying without adequate removal by suction.
Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.
Not necessary if room is well-ventilated.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove
material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 5)

**For the permanent contact
gloves made of the following
materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture the penetration time has to be at least 480 minutes
(Permeation according to EN 374 Part 3: Level 6).

**As protection from splashes
gloves made of the following
materials are suitable:**

Nitrile rubber, NBR

Eye protection:

Goggles recommended during refilling

Body protection:

Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:

Fluid

Colour:

According to product specification

Odour:

Mild

Odour threshold:

Not determined

pH-value:

8-9

Change in condition

Melting point/freezing point:

Undetermined

Initial boiling point and boiling range: 100 °C**Flash point:**

Not applicable

Flammability

Not applicable

Decomposition temperature:

Not determined

Ignition temperature:

Product is not selfigniting.

Explosive properties:

Product does not present an explosion hazard.

Explosion limits:**Lower:**

Not determined

Upper:

Not determined

Vapour pressure at 20 °C:

23 hPa

Density at 20 °C:1.10 - 1.25 g/cm³ (DIN 53217)**Relative density**

Not determined

Evaporation rate

Not determined

(Contd. on page 7)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 6)

Solubility in / Miscibility with water:

Fully miscible.

Partition coefficient: n-octanol/water: Not determined**Viscosity:****Dynamic at 20 °C:** 1,300–1,700 mPas**Other information**

No further relevant information available.

10 Stability and reactivity**Reactivity**

No further relevant information available.

Chemical stability**Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

No dangerous reactions known.

Conditions to avoid

No further relevant information available.

Incompatible materials:

No further relevant information available.

Hazardous decomposition products:Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)**11 Toxicological information****Information on toxicological effects****Acute toxicity****LD/LC50 values relevant for classification:****CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one**

Oral	LD50	450 mg/kg (ATE) >5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	0.21 mg/l (ATE)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	64 mg/kg (rat)
Dermal	LD50	78 mg/kg (rabbit)
Inhalative	LC50 / 4h	0.05 mg/l (ATE)
	ATE-Wert (Dampf)	1 mg/l

(Contd. on page 8)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 7)

Primary irritant effect:**Skin corrosion/irritation**

No irritant effect.

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Irritating effect.

Respiratory or skin**sensitisation**

May cause an allergic skin reaction.

Subacute to chronic toxicity:

Based on available data, the classification criteria are not met.

Additional toxicological**information:**

Irritant

Sensitisation

May cause an allergic skin reaction.

12 Ecological information

Toxicity**Aquatic toxicity:****CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one**

EC50/ 72h	0.15 mg/l (algae)
LC50 / 96h	1.3–1.6 mg/l (fish)
LC50 / 48h	1.5–3.3 mg/l (Daphnia magna)
NOEC / 3 days	0.0403 mg/l (algae)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50 / 48h	0.16 mg/l (Daphnia magna)
LC50 / 96h	0.19 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
biodegradability	>60 %

Persistence and degradability No further relevant information available.**Behaviour in environmental systems:****Bioaccumulative potential****CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)**

log POW	≤0.71–0.75
---------	------------

Mobility in soil

No further relevant information available.

Ecotoxicological effects:**Behaviour in sewage processing plants:****CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)**

EC50	7.9 mg/l (activated sludge organism)
------	--------------------------------------

(Contd. on page 9)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 8)

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods**Recommendation**

Do not clean empty packaging before disposal.
 Paint must not be flushed down the drain, not even when cleaning painting tools.
 Consumers: Dispose of paint leftovers at your local household hazardous waste collection point.
 Professionals: Dispose of paint leftovers by contracting a waste management company.
 For information on the prevention of the release of synthetic polymer particles see Section 15

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Recommended cleansing**agents:**

Water, if necessary together with cleansing agents.

14 Transport information

UN-Number

ADR, ADN, IMDG, IATA

Not applicable

UN proper shipping name

ADR, ADN, IMDG, IATA

Not applicable

Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

Not applicable

Packing group

ADR, IMDG, IATA

Not applicable

Environmental hazards:

Marine pollutant:

No

(Contd. on page 10)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 9)

Special precautions for user	Not applicable
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable
UN "Model Regulation":	Not applicable

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

CAS: 7664-41-7	ammonia, anhydrous	Listed
CAS: 1310-58-3	potassium hydroxide	17% of total caustic alkalinity
CAS: 1310-73-2	sodium hydroxide	12% of total caustic alkalinity

GHS label elements Void**Hazard pictograms** Void**Signal word** Void**Hazard statements** Void**Precautionary statements** P102 Keep out of reach of children.

Chemical safety assessment

Named dangerous

substances - ANNEX I None of the ingredients is listed.**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H310 Fatal in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.

(Contd. on page 11)

Safety data sheet

according to UK REACH

Printing date 24.03.2026

Version number 7.0

Revision: 13.03.2026

Trade name: Interior-Wax

(Contd. of page 10)

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Classification according to**Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 2: Acute toxicity – Category 2
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Sources

ECHA Portal
 Safety data sheets from raw material suppliers
 ESIS : European chemical Substances Information System

*** Data compared to the
 previous version altered.**

Additions, Deletions, Revisions
 Updated according to regulation (EU) 2020/878 amending regulation (EC) No: 1907/2006 (UK REACH)