

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

1 Identification of the substance/mixture and of the company/undertaking

Product identifier**Trade name:** Wood Reviver Power-Gel**Article number:** 6609**Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture

Surface cleanser

Details of the supplier of the safety data sheet**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany**Further information obtainable from:**Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de**Emergency telephone number:**IE: National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)
Healthcare Professionals: +353 (1) 809 2566 (24 hour service)
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111
emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English**Importer**Importer for UK:
OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com
United Kingdom

2 Hazards identification

Classification of the substance or mixture

Eye Dam. 1 H318 Causes serious eye damage.

Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 2)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 1)

Label elements**Hazard pictograms**

GHS05

Signal word

Danger

Hazard-determining**components of labelling:**

oxalic acid

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P280 Wear eye protection / face protection.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

Additional information:

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Other hazards

Protect metals (e.g. fittings) and plants from direct contact (e.g. cover useful and ornamental plants with painters' foil).

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment**PBT:** Not applicable**vPvB:** Not applicable

3 Composition/information on ingredients

Chemical characterisation: Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

-GB

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 3)

For safety reasons unsuitable
extinguishing agents: For this mixture there are no extinguishing agent restrictions.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters
Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for
containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Warm water and cleansing agent

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:
Precautions for safe handling When diluting always pour product into water and not vice versa.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with skin and eyes.

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection:

No special measures required.

(Contd. on page 5)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 4)

Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by

storerooms and receptacles: Unsuitable material for receptacle: aluminium.
 Unsuitable material for receptacle: steel.
 Store only in the original receptacle.

Information about storage in

one common storage facility: Store away from oxidising agents.
 Store away from reducing agents.

Further information about

storage conditions: Protect from frost.
 Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters
**Ingredients with limit values
 that require monitoring at the
 workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	0.09 mg/kgKG/Tag
	DNEL Verbraucher (AKUT - systemische Effekte)	0.11 mg/kgKG/Tag
Inhalative	DNEL Arbeitnehmer (Langzeit - lokale Effekte)	0.02 mg/m ³
	DNEL Verbraucher (Langzeit - lokale Effekte)	0.02 mg/m ³

PNECs

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

PNEC sea water	0.00339 mg/l
PNEC fresh water	0.0039 mg/l
PNEC sediment (fresh water)	0.027 mg/kg
PNEC sediment (sea water)	0.027 mg/kg
PNEC soil	0.01 mg/kg

Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 5)

Exposure controls**Personal protective equipment:**
**General protective and
hygienic measures:**

Do not eat or drink while working.
 Avoid contact with the eyes and skin.
 The usual precautionary measures are to be adhered to when handling chemicals.
 Do not eat, drink, smoke or sniff while working.
 See Section 7 for information on safe handling.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
 Check protective gloves prior to each use for their proper condition.
 Preventive skin protection by use of skin-protecting agents is recommended.
 Protective gloves
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
 As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove
material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**As protection from splashes
gloves made of the following
materials are suitable:**

Nitrile rubber, NBR

Eye protection:

Tightly sealed goggles

Body protection:

Acid resistant protective clothing
 Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information**Appearance:**
Form: Pasty

(Contd. on page 7)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 6)

Colour:	Light green
Odour:	Mild
Odour threshold:	Not determined
pH-value at 20 °C:	>2.1
Change in condition	
Melting point/freezing point:	Undetermined
Initial boiling point and boiling range:	100 °C
Flash point:	Not applicable
Flammability	Not applicable
Decomposition temperature:	Not determined
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined
Upper:	Not determined
Vapour pressure at 20 °C:	23 hPa
Density at 20 °C:	1.09 g/cm ³ (DIN 51757)
Relative density	Not determined
Evaporation rate	Not determined
Solubility in / Miscibility with water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined
Viscosity:	
Dynamic:	Not determined
Solvent content:	
VOC (EC)	Not applicable.
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability
Thermal decomposition /
conditions to be avoided: No decomposition if used and stored according to specifications.

(Contd. on page 8)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 7)

Possibility of hazardous reactions

No dangerous reactions known.

Conditions to avoid

No further relevant information available.

Incompatible materials:

No further relevant information available.

Hazardous decomposition products:

No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects
Acute toxicity
LD/LC50 values relevant for classification:
ATE (Acute Toxicity Estimates)

Oral	LD50	5,682 mg/kg (rat)
Dermal	LD50	16,667 mg/kg

CAS: 6153-56-6 oxalic acid

Oral	LD50	375 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rat)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	64 mg/kg (rat)
Dermal	LD50	78 mg/kg (rabbit)
Inhalative	LC50 / 4h	0.05 mg/l (ATE)
	ATE-Wert (Dampf)	1 mg/l

Primary irritant effect:
CAS: 6153-56-6 oxalic acid

Irritation of skin	Schleimhautreizung	
--------------------	--------------------	--

Skin corrosion/irritation
CAS: 6153-56-6 oxalic acid

Dermal	Skin irritation	
--------	-----------------	--

Serious eye damage/irritation Irritating effect.

CAS: 6153-56-6 oxalic acid

Eye irritation	
----------------	--

Respiratory or skin sensitisation
CAS: 6153-56-6 oxalic acid

Inhalative	sensitization	
------------	---------------	--

Subacute to chronic toxicity: Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 8)

Additional toxicological information:

 Harmful
Irritant

12 Ecological information

Toxicity
Aquatic toxicity:
CAS: 6153-56-6 oxalic acid

EC50 / 48h	162.2 mg/l (Daphnia magna)
LC50 / 96h	160 mg/l (fish)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50 / 48h	0.16 mg/l (Daphnia magna)
LC50 / 96h	0.19 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
biodegradability	>60 %

Persistence and degradability No further relevant information available.

Behaviour in environmental systems:
Bioaccumulative potential
CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

log POW	≤0.71–0.75
---------	------------

Mobility in soil No further relevant information available.

Ecotoxicological effects:
Behaviour in sewage processing plants:
CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50	7.9 mg/l (activated sludge organism)
------	--------------------------------------

Additional ecological information:
General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Results of PBT and vPvB assessment
PBT: Not applicable

vPvB: Not applicable

Other adverse effects No further relevant information available.

(Contd. on page 10)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 9)

13 Disposal considerations

Waste treatment methods
Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

Uncleaned packaging:
Recommendation:

Disposal must be made according to official regulations.

Recommended cleansing agents:

Water, if necessary together with cleansing agents.

14 Transport information

UN-Number ADR, ADN, IMDG, IATA	Not applicable
UN proper shipping name ADR, ADN, IMDG, IATA	Not applicable
Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Not applicable
Packing group ADR, IMDG, IATA	Not applicable
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable
UN "Model Regulation":	Not applicable

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

(Contd. on page 11)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 10)

Poisons Act**Regulated explosives precursors**

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

CAS: 7631-99-4	sodium nitrate, containing in the dry state more than 16,3 per cent by weight of nitrogen	Listed
----------------	---	--------

Reportable poisons

None of the ingredients is listed.

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

GHS05

Signal word

Danger

Hazard-determining components of labelling:

oxalic acid

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear eye protection / face protection.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H310 Fatal in contact with skin.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.

(Contd. on page 12)

Safety data sheet

according to UK REACH

Printing date 12.03.2026

Version number 7.1

Revision: 10.03.2026

Trade name: Wood Reviver Power-Gel

(Contd. of page 11)

H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Classification according to**Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route
 (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 2: Acute toxicity – Category 2
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Sources

ESIS : European chemical Substances Information System
 ECHA Portal
 Safety data sheets from raw material suppliers

*** Data compared to the
 previous version altered.**

Additions, Deletions, Revisions
 Updated according to regulation (EU) 2020/878 amending regulation (EC) No:
 1907/2006 (UK REACH)