

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

### 1 Identification of the substance/mixture and of the company/undertaking

**Product identifier****Trade name:** Natural Oil Woodstain Effect**Article number:** 1140, 1142, 1143**Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture**

Paint

Coating compound/ Surface coating/ paint

**Details of the supplier of the safety data sheet****Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf  
Germany**Further information obtainable from:**Product safety department  
Tel.: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de**Emergency telephone number:**

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

**Importer**Importer for UK:  
OSMO UK,  
Smeaton Close  
Unit 24 Anglo Business Park  
Aylesbury, Bucks HP19 8UP  
Phone: 01296 481 220, www.osmouk.com  
United Kingdom

### 2 Hazards identification

**Classification of the substance or mixture**

Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

**Additional information:** For the wording of the listed hazard phrases refer to section 16.**Label elements****Hazard pictograms**

GHS02

**Signal word**

Warning

**Hazard statements**

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 2)

|                                                                                                 |                                                                                                                                                                                                      |             |
|-------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| CAS: 84418-68-8<br>EINECS: 282-780-4                                                            | Neodecanoic acid, zinc salt, basic<br>Aquatic Acute 1, H400; Aquatic Chronic 2, H411                                                                                                                 | ≥0.25–≤1%   |
| CAS: 55406-53-6<br>EINECS: 259-627-5<br>Index number: 616-212-00-7<br>Reg.nr.: 01-2119489924-20 | 3-Iodo-2-propynylbutylcarbamate<br>Acute Tox. 2, H330; STOT RE 1, H372; Eye Dam. 1, H318;<br>Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10);<br>Acute Tox. 4, H302; Skin Sens. 1, H317 | ≥0.1–<0.25% |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

##### Description of first aid measures

###### General information:

Take affected persons out into the fresh air.  
Immediately remove any clothing soiled by the product.

###### After inhalation:

Supply fresh air; consult doctor in case of complaints.  
In case of unconsciousness place patient stably in side position for transportation.

###### After skin contact:

Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.  
If skin irritation or rash occurs: Get medical advice/attention.

###### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

###### After swallowing:

Induce vomiting only, if affected person is fully conscious.  
If swallowed, seek medical advice immediately and show this container or label.  
Do NOT induce vomiting.

###### Information for doctor:

###### Most important symptoms and effects, both acute and delayed

Headache  
Dizziness

###### Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

#### 5 Firefighting measures

##### Extinguishing media

###### Suitable extinguishing

###### agents:

CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

###### For safety reasons unsuitable

###### extinguishing agents:

Water with full jet

###### Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 3)

**Advice for firefighters****Protective equipment:****Additional information**

Carbon monoxide (CO)  
carbon dioxide (CO<sub>2</sub>)

Mouth respiratory protective device.  
Do not inhale explosion gases or combustion gases.  
Wear self-contained respiratory protective device.  
General measures for chemical fires.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.  
Cool endangered receptacles with water spray.

## 6 Accidental release measures

**Personal precautions,  
protective equipment and  
emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources.  
Wear protective clothing.

**Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

**Methods and material for**

**containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).  
Dispose of the material collected according to regulations.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.

**Reference to other sections**

Do not flush with water or aqueous cleansing agents  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

**Handling:**

Even a small sip can lead to life-threatening damage to the lungs. Keep rags filled with this liquid out of the reach of children.

**Precautions for safe handling**

Use only in well ventilated areas.  
Keep away from heat and direct sunlight.  
Keep receptacles tightly sealed.  
Prevent formation of aerosols.  
Open and handle receptacle with care.  
Avoid contact with skin and eyes.

(Contd. on page 5)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 4)

**General protective and hygienic measures:**

Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes and skin.  
 Do not eat, drink, smoke or sniff while working.  
 Do not carry product impregnated cleaning cloths in trouser pockets.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Conditions for safe storage, including any incompatibilities**
**Storage:**
**Requirements to be met by**

**storerooms and receptacles:** Store only in the original receptacle.  
 Store in a cool location.

**Information about storage in**

**one common storage facility:** Not required

**Further information about**
**storage conditions:**

Store receptacle in a well ventilated area.  
 Keep container tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.

**Storage class:**

TRGS 510 Storage class 3: Flammable liquids

**Specific end use(s)**

No further relevant information available.

## 8 Exposure controls/personal protection

**Control parameters**
**Ingredients with limit values that require monitoring at the workplace:**

**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

|     |                                                 |
|-----|-------------------------------------------------|
| WEL | Long-term value: 308 mg/m <sup>3</sup> , 50 ppm |
| Sk  |                                                 |

**DNELs**

**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

|            |                                                   |                        |
|------------|---------------------------------------------------|------------------------|
| Oral       | DNEL Verbraucher (Langzeit - systemische Effekte) | 36 mg/kgKG/Tag         |
| Dermal     | DNEL Verbraucher (Langzeit - systemische Effekte) | 121 mg/cm <sup>2</sup> |
| Inhalative | Worker (chronic - Systemic health effec)          | 308 mg/m <sup>3</sup>  |
|            | DNEL Verbraucher (Lanzeit - systemische Effekte)  | 37.2 mg/m <sup>3</sup> |

(Contd. on page 6)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 5)

**CAS: 7429-90-5 aluminium powder (stabilised)**

|            |                                                   |                        |
|------------|---------------------------------------------------|------------------------|
| Oral       | DNEL Verbraucher (Langzeit - systemische Effekte) | 3.95 mg/kgKG/Tag       |
| Inhalative | Worker (chronic - Systemic health effec)          | 3.72 mg/m <sup>3</sup> |
|            | DNEL Arbeitnehmer (Langzeit - lokale Effekte)     | 3.72 mg/m <sup>3</sup> |

**PNECs**
**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

|                             |            |
|-----------------------------|------------|
| PNEC sea water              | 1.9 mg/l   |
| PNEC fresh water            | 19 mg/l    |
| PNEC sediment (fresh water) | 70.2 mg/kg |
| PNEC sediment (sea water)   | 7.02 mg/kg |
| PNEC soil                   | 2.74 mg/kg |
| PNEC sewage treatment plant | 4,168 mg/l |
| interrupted release         | 190 mg/l   |

**CAS: 7429-90-5 aluminium powder (stabilised)**

|                             |             |
|-----------------------------|-------------|
| PNEC fresh water            | 0.0749 mg/l |
| PNEC sewage treatment plant | 20 mg/l     |

**Additional information:** The lists valid during the making were used as basis.

**Exposure controls**
**Personal protective equipment:**
**General protective and**
**hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Avoid contact with the eyes and skin.  
 Immediately remove all soiled and contaminated clothing  
 Do not inhale gases / fumes / aerosols.  
 The usual precautionary measures are to be adhered to when handling chemicals.  
 Do not eat, drink, smoke or sniff while working.  
 Do not carry product impregnated cleaning cloths in trouser pockets.  
 See Section 7 for information on safe handling.

**Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed.  
 Not necessary if room is well-ventilated.  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
 Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.  
 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Protection of hands:**

Protective gloves

(Contd. on page 7)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 6)

**Material of gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

**As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

Tightly sealed goggles

**Body protection:**

Protective work clothing

## 9 Physical and chemical properties

**Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Fluid

**Colour:**

According to product specification

**Odour:**

Mild

**Odour threshold:**

Not determined

**pH-value:**

Mixture is non-polar/aprotic.  
Not applicable

**Change in condition****Melting point/freezing point:**

Undetermined

**Initial boiling point and boiling range:**

&gt;180 °C

**Flash point:**

43-59 °C (DIN EN ISO 2719)

**Flammability**

Flammable.

(Contd. on page 8)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 7)

|                                                |                                            |
|------------------------------------------------|--------------------------------------------|
| <b>Auto-ignition temperature:</b>              | 240 °C                                     |
| <b>Decomposition temperature:</b>              | Not determined                             |
| <b>Ignition temperature:</b>                   | Product is not selfigniting.               |
| <b>Explosive properties:</b>                   | Not determined                             |
| <b>Explosion limits:</b>                       |                                            |
| <b>Lower:</b>                                  | 0.6 Vol %                                  |
| <b>Upper:</b>                                  | 7 Vol %                                    |
| <b>Vapour pressure:</b>                        | Not determined                             |
| <b>Density at 20 °C:</b>                       | 1 g/cm <sup>3</sup> (DIN 51757)            |
| <b>Relative density</b>                        | Not determined                             |
| <b>Evaporation rate</b>                        | Not determined                             |
| <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.          |
| <b>Partition coefficient: n-octanol/water:</b> | Not determined                             |
| <b>Viscosity:</b>                              |                                            |
| <b>Dynamic:</b>                                | Not determined                             |
| <b>Other information</b>                       | No further relevant information available. |

### 10 Stability and reactivity

|                                                          |                                                                                                                                                     |
|----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Reactivity</b>                                        | No further relevant information available.                                                                                                          |
| <b>Chemical stability</b>                                |                                                                                                                                                     |
| <b>Thermal decomposition / conditions to be avoided:</b> | No decomposition if used and stored according to specifications.                                                                                    |
| <b>Possibility of hazardous reactions</b>                | Reacts with fabric soaked in the product (e.g. cleaning wool).<br>Reacts with acids, alkalis and oxidising agents.                                  |
| <b>Conditions to avoid</b>                               | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                                      |
| <b>Incompatible materials:</b>                           | No further relevant information available.                                                                                                          |
| <b>Hazardous decomposition products:</b>                 | Carbon monoxide and carbon dioxide<br>Nitrogen oxides (NO <sub>x</sub> )<br>Formation of toxic gases is possible during heating or in case of fire. |

(Contd. on page 9)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 8)

## 11 Toxicological information

### Information on toxicological effects

#### Acute toxicity

#### LD/LC50 values relevant for classification:

#### ATE (Acute Toxicity Estimates)

|      |      |                             |
|------|------|-----------------------------|
| Oral | LD50 | 44,466–<101,749 mg/kg (rat) |
|------|------|-----------------------------|

  

|                                                                                                          |           |                    |
|----------------------------------------------------------------------------------------------------------|-----------|--------------------|
| <b>CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics &lt; 2 %</b> |           |                    |
| Oral                                                                                                     | LD50      | >5,000 mg/kg (rat) |
| Dermal                                                                                                   | LD50      | >5,000 mg/kg (rat) |
| Inhalative                                                                                               | LC50 / 4h | >5 mg/l (rat)      |

  

|                                                            |            |                                                   |
|------------------------------------------------------------|------------|---------------------------------------------------|
| <b>CAS: 34590-94-8 Dipropylene glycol monomethyl ether</b> |            |                                                   |
| Oral                                                       | LD50       | >5,000 mg/kg (rat)                                |
| Dermal                                                     | LD50       | 9,500 mg/kg (rat)<br>13,000–14,000 mg/kg (rabbit) |
| Inhalative                                                 | LC50 / 4h  | 1,667 mg/l (rat)                                  |
|                                                            | LC50 / 72h | 0.76 mg/l (selenastrum capricornutum)             |

  

|                                                                                                                                                     |      |                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|------|-------------------|
| <b>CAS: 127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates</b> |      |                   |
| Oral                                                                                                                                                | LD50 | 2,000 mg/kg (rat) |

  

|                                                           |            |                                            |
|-----------------------------------------------------------|------------|--------------------------------------------|
| <b>CAS: 84418-68-8 Neodecanoic acid, zinc salt, basic</b> |            |                                            |
| Oral                                                      | LD50       | >5,000 mg/kg (rat) (Acute Oral Toxicity)   |
| Dermal                                                    | LD50       | >3,640 mg/kg (rat) (Acute Dermal Toxicity) |
|                                                           | LC50 / 72h | 2.05 mg/l (algae)                          |

  

|                                                        |           |                    |
|--------------------------------------------------------|-----------|--------------------|
| <b>CAS: 55406-53-6 3-Iodo-2-propynylbutylcarbamate</b> |           |                    |
| Oral                                                   | LD50      | 500 mg/kg (rat)    |
| Dermal                                                 | LD50      | >2,000 mg/kg (rat) |
| Inhalative                                             | LC50 / 4h | 0.05 mg/l (ATE)    |

#### Primary irritant effect:

#### Skin corrosion/irritation

No irritant effect.

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Irritating effect.

#### Respiratory or skin

#### sensitisation

Sensitising effect by skin contact is possible by prolonged exposure.

#### Subacute to chronic toxicity:

Based on available data, the classification criteria are not met.

(Contd. on page 10)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 9)

## 12 Ecological information

### Toxicity

#### Aquatic toxicity:

**CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %**

EC50 / 48h &gt;1,000 mg/l (Daphnia magna)

IC50 / 72h &gt;1,000 mg/l (algae)

LC50 / 96h &gt;1,000 mg/l (fish)

**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

EC50 / 48h 70.2 mg/l

1,919 mg/l (Daphnia magna)

EC50/ 72h &gt;969 mg/l (algae)

LC50 / 96h &gt;10,000 mg/l (aquatic vertebrates - in vivo)

&gt;1,000 mg/l (fish)

5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

LC50 / 48h 1,919 mg/l (daphnia)

10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

**CAS: 127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates**

EC50 / 48h 3.2 mg/l (Daphnia magna) (24h EC 50 acute immobilisation test)

Bioconceived factor &lt;3 (Flow-through fish test)

**CAS: 84418-68-8 Neodecanoic acid, zinc salt, basic**

IC50/ 3h 5.2 mg/l (activated sludge organism) (Activated Sludge, Respiration Inhibition Test)

LC50 / 96h 0.112 mg/l (fish)

NOEC / 3 days 0.06 mg/l (algae)

**CAS: 55406-53-6 3-Iodo-2-propynylbutylcarbamate**

EC50 / 48h 0.16 mg/l (Daphnia magna)

EC50/ 72h 0.022 mg/l (algae)

**Persistence and degradability** No further relevant information available.

**Behaviour in environmental systems:**
**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

**Ecotoxicological effects:**
**Remark:** Harmful to aquatic life with long lasting effects.

Harmful to fish

(Contd. on page 11)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 10)

**Behaviour in sewage processing plants:**
**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

EC50/ 96h | 969 mg/l (algae)

**CAS: 55406-53-6 3-Iodo-2-propynylbutylcarbamate**

EC50/ 96h | 0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

**Additional ecological information:**

**General notes:** Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
 Danger to drinking water if even small quantities leak into the ground.  
 Harmful to aquatic organisms

**Results of PBT and vPvB assessment**
**PBT:** Not applicable

**vPvB:** Not applicable

**Other adverse effects** No further relevant information available.

### 13 Disposal considerations

**Waste treatment methods**
**Recommendation**

Do not clean empty packaging before disposal.  
 Paint must not be flushed down the drain, not even when cleaning painting tools.  
 Consumers: Dispose of paint leftovers at your local household hazardous waste collection point.  
 Professionals: Dispose of paint leftovers by contracting a waste management company.  
 For information on the prevention of the release of synthetic polymer particles see Section 15

**Uncleaned packaging:**
**Recommendation:**

Disposal must be made according to official regulations.

**Recommended cleansing agents:**

Solvent naphtha  
 Osmo Brush Cleaner and Thinner

### 14 Transport information

**UN-Number**

ADR, IMDG, IATA

UN1263

**UN proper shipping name**

ADR

1263 PAINT

IMDG, IATA

PAINT

(Contd. on page 12)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 11)

|                                                                           |                                                   |
|---------------------------------------------------------------------------|---------------------------------------------------|
| <b>Transport hazard class(es)</b>                                         |                                                   |
| <b>ADR</b>                                                                |                                                   |
| <b>Class</b>                                                              | 3 (F1) Flammable liquids.                         |
| <b>Label</b>                                                              | 3                                                 |
| <hr/>                                                                     |                                                   |
| <b>IMDG, IATA</b>                                                         |                                                   |
| <b>Class</b>                                                              | 3 Flammable liquids.                              |
| <b>Label</b>                                                              | 3                                                 |
| <hr/>                                                                     |                                                   |
| <b>Packing group</b>                                                      |                                                   |
| <b>ADR, IMDG, IATA</b>                                                    | III                                               |
| <hr/>                                                                     |                                                   |
| <b>Environmental hazards:</b>                                             |                                                   |
| <b>Marine pollutant:</b>                                                  | No                                                |
| <hr/>                                                                     |                                                   |
| <b>Special precautions for user</b>                                       | Warning: Flammable liquids.                       |
| <b>Hazard identification number (Kemler code):</b>                        | 30                                                |
| <b>EMS Number:</b>                                                        | F-E, S-E                                          |
| <b>Stowage Category</b>                                                   | A                                                 |
| <hr/>                                                                     |                                                   |
| <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b> |                                                   |
| Not applicable                                                            |                                                   |
| <hr/>                                                                     |                                                   |
| <b>Transport/Additional information:</b>                                  |                                                   |
| <hr/>                                                                     |                                                   |
| <b>ADR</b>                                                                |                                                   |
| <b>Limited quantities (LQ)</b>                                            | 5L                                                |
| <b>Excepted quantities (EQ)</b>                                           | Code: E1                                          |
|                                                                           | Maximum net quantity per inner packaging: 30 ml   |
|                                                                           | Maximum net quantity per outer packaging: 1000 ml |
| <b>Transport category</b>                                                 | 3                                                 |
| <b>Tunnel restriction code</b>                                            | D/E                                               |
| <hr/>                                                                     |                                                   |
| <b>IMDG</b>                                                               |                                                   |
| <b>Limited quantities (LQ)</b>                                            | 5L                                                |
| <b>Excepted quantities (EQ)</b>                                           | Code: E1                                          |
|                                                                           | Maximum net quantity per inner packaging: 30 ml   |
|                                                                           | Maximum net quantity per outer packaging: 1000 ml |
| <hr/>                                                                     |                                                   |
| <b>UN "Model Regulation":</b>                                             | UN 1263 PAINT, 3, III                             |

(Contd. on page 13)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 12)

### 15 Regulatory information

**Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**Poisons Act**

**Regulated explosives precursors**

None of the ingredients is listed.

**Regulated poisons**

None of the ingredients is listed.

**Reportable explosives precursors**

|                |                               |        |
|----------------|-------------------------------|--------|
| CAS: 7429-90-5 | aluminium powder (stabilised) | Listed |
|----------------|-------------------------------|--------|

**Reportable poisons**

None of the ingredients is listed.

**GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

**Hazard pictograms**


GHS02

**Signal word**

Warning

**Hazard statements**

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

|           |                                                                        |
|-----------|------------------------------------------------------------------------|
| P101      | If medical advice is needed, have product container or label at hand.  |
| P102      | Keep out of reach of children.                                         |
| P210      | Keep away from heat. - No smoking.                                     |
| P273      | Avoid release to the environment.                                      |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed.       |
| P501      | Dispose of contents/container in accordance with national regulations. |

**Chemical safety assessment**
**Named dangerous**
**substances - ANNEX I**

None of the ingredients is listed.

**Seveso category**

P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes)  
for the application of lower-  
tier requirements**

5,000 t

**Qualifying quantity (tonnes)  
for the application of upper-  
tier requirements**

50,000 t

**Information about limitation of use:**
**GISBAU-Code**

GISCODE: Ö60

(Contd. on page 14)

## Safety data sheet

### according to UK REACH

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 13)

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H228 Flammable solid.  
 H261 In contact with water releases flammable gases.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H330 Fatal if inhaled.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.

**Classification according to**

**Regulation (EC) No 1272/2008** The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Department issuing SDS:**

product safety department

**Contact:**

Hr. Dr. Starp

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route  
 (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 ATE: Acute toxicity estimate values  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Flam. Sol. 1: Flammable solids – Category 1  
 Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2  
 Acute Tox. 4: Acute toxicity – Category 4  
 Acute Tox. 2: Acute toxicity – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Skin Sens. 1: Skin sensitisation – Category 1  
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. on page 15)

**Safety data sheet**  
**according to UK REACH**

Printing date 17.02.2026

Version number 10.1

Revision: 13.02.2026

**Trade name: Natural Oil Woodstain Effect**

(Contd. of page 14)

**Sources**

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

ECHA Portal

Safety data sheets from raw material suppliers

ESIS : European chemical Substances Information System

**\* Data compared to the  
previous version altered.**

Additions, Deletions, Revisions

Updated according to regulation (EU) 2020/878 amending regulation (EC) No:  
1907/2006 (UK REACH)

GB