


PRODUCT INFORMATION

PAINT STRIPPER

FOR WOOD AND METAL



6000 Clear



PRODUCT DESCRIPTION:

Osmo Paint Stripper is a powerful, low odour, universal paint stripper for solvent-resistant substrates. Thanks to its long open time, it can dissolve several layers of lacquer or varnish in one work step. The paint stripper gel is free of aromatic compounds and chlorinated hydrocarbons.

RECOMMENDED USE:

Dissolves and removes synthetic resin lacquers, 1-component lacquers, dispersion and latex paints, oil finishes and wood stains, dispersion glues, polymer plasters etc. on solvent-resistant substrates (wood, metal, mineral substrates, such as render, concrete or stone). It has a mild odour and therefore it can be used on large areas in both indoor and outdoor areas.

INGREDIENTS:

Aliphatic ester, N-n-Butylpyrrolidone, organic acid (formic acid) and additives.

TECHNICAL DATA:

Specific weight: 1.020-1.100 g/cm³ (DIN ISO 2811-2)
Viscosity: 2500-3500 mPas
Odour: faint/mild, odourless after drying
Flashpoint: > 100 °C, acc. DIN EN ISO 2719

STORAGE:

2 years or longer if stored in the originally closed container.

SURFACE PREPARATION:

Always test on a small area first to determine performance, reaction time, substrate compatibility and material requirements! Cover and tape up any surfaces not to be treated, plastics (piping, wiring, windows etc.) as well as plants. Wear appropriate protective clothing and safety goggles when working.

METHODS OF APPLICATION:

Stir well – do not thin. Apply generously and evenly with a brush or trowel and cover immediately with a thin foil (e.g. polythene dust sheets) and allow for sufficient reaction time (depending on project a few minutes/several hours/possibly overnight). Test stripping performance occasionally with a trowel. Always remove dissolved coating layer at the optimal time. Do not leave Osmo Paint Stripper on substrates for longer than necessary. Reaction time depends on the coating type, coating thickness and ambient temperature. Remove the soft dissolved layer with a trowel and rinse with water (if possible warm, approx. 40°C). In some cases, it may be necessary to repeat the application.

CLEANING OF TOOLS:

With soap and water.

DRYING TIME:

Before applying a new coating, allow the wood to dry thoroughly (approx. 24-48 hours). Lower temperatures and/or higher air humidity may increase drying times significantly.

PRODUCT INFORMATION

PAINT STRIPPER

COVERAGE:

Product coverage for 1 coat is 2-4 m²/l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

NOTE:

In indoor areas, always work with foils and ventilate well. Not suitable for highly crosslinked lacquers, such as 2-component DD coatings or epoxy resin coatings.

CAUTION:

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wash hands thoroughly after handling. Wear protective gloves/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. Contains N-n-Butylpyrrolidone, formic acid.

Always follow the information on the product label.



Warning

DISPOSAL:

Do not release product or wastewater into the ground. Collect coating residues and dispose as according to the

requirements of the local authorities. Dispose of leftover product and completely emptied packaging according to official guidelines (waste code number 08 01 21*). Only completely emptied cans can be recycled.

COLOUR TONE:

6000 Clear

SIZE:

1.0 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information.

For information specific to a certain country or region, please consult your local wholesaler or dealer:

OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26