


PRODUCT INFORMATION

COUNTRY COLOUR

VARIETY OF COLOURS AND UNSURPASSED DURABILITY – FOR ALL WEATHER CONDITIONS!

				
2310 White Satin	2203 Light Ochre Satin	2204 Ivory Satin	2205 Sunflower Yellow Satin	2308 Nordic Red Satin
				
2310 Cedar/Redwood Satin	2311 Signal Red Satin	2404 Fir Green Satin	2501 Labrador Blue Satin	2506 Royal Blue Satin
				
2507 Dove Blue Satin	2606 Medium Brown Satin	2607 Dark Brown Satin	2703 Charcoal Satin	2704 Dusk Grey Satin
				
2708 Pebble Grey Satin	2716 Anthracite Grey Satin	2735 Light Grey (RAL 7035) Satin	2742 Traffic Grey A (RAL 7042) Satin	



PRODUCT DESCRIPTION:

Opaque, at first slightly satin-gloss then satin wood finish. Wood tone and grain is covered. The wood texture remains noticeable. Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent, extremely weatherproof and UV stable surface does not crack, peel, flake or blister. No sanding necessary, just simply recoat; no primer is needed. Easy and seamless application. Finish stays workable while coating. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3). Wood colour and grain are covered. The wood texture stays noticeable.

RECOMMENDED USE:

Osmo Country Colour is best suited for all wood in outdoor areas, where an especially durable, satin, opaque, biocide-free coating is required: timber cladding, balconies, windows and window shutters, fences, pergolas, wooden shingles, garden furniture and

garden sheds, carports etc. Ideal for renewing old microporous finishes and weathered wooden surfaces.

INGREDIENTS:

Binding agent based on natural plant oils (sunflower oil, soybean oil and thistle oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Dearomatised white spirit (benzene-free). Detailed declaration of ingredients available upon request.

TECHNICAL DATA:

Specific weight: 0.880-1.300 g/cm³ (DIN ISO 2811-2)
Viscosity: 25-60s (DIN 53211/4mm)
Odour: faint/mild, odourless after drying
Flashpoint: > 100°C (DIN EN ISO 2719)

STORAGE:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use.

PRODUCT INFORMATION

COUNTRY COLOUR

SURFACE PREPARATION:

Wood surface must be clean, dry and frost-free (moisture content max. 20%). Osmo Country Colour is ready to use. Do not thin. Stir well before use. If possible, please apply the first coat to all sides before installation. Clean old microporous stains thoroughly. Old paints, varnishes and lacquers must be completely removed. Always wear dust mask while sanding.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION:

With Osmo Flat Brush or Osmo Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and spread well. Allow to dry for approx. 10-12 hours under good ventilation. After drying, apply a second coat – also thinly. When renovating, one coat applied to the clean and dry surface is usually sufficient.

CLEANING OF TOOLS:

With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME:

Approx. 12 hours (normal climatic conditions, 20–23°C / 50–65 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

COVERAGE:

Product coverage for 1 coat is 26 m²/l. It depends significantly on the condition of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

RECOMMENDATION:

Ready to use – do not thin! Apply to the clean wood thinly with Osmo Flat Brush, Finish Applicator Fleece or Microfibre Roller and spread well along the wood grain. The coating results depend on several factors, including the condition of the wood and the wood moisture content (max. 20%). Therefore, a trial application is always required, especially for unfamiliar surfaces.

If additional protection, for example, against rot, blue stain or insect attack is required, the untreated wood

should be pre-treated with Osmo WR Base Coat – on all sides if possible – before the first coat is applied.

Depending on the desired level of protection, you can choose a variant containing biocidal active ingredients (chemical wood preservation) or one without biocides (physical wood preservation). It is essential to adhere to the drying times specified in the relevant product information.

NOTE:

Country Colour, which has been trusted for over decades, is also available in the colour of your choice. Starting from 2.5 litres per colour tone, available in 186 RAL Classic and 1950 NCS colour tones, as well as with biocidal film protection additives. Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

CAUTION:

Keep out of reach of children. Safety data sheet available on request. Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly. EU limit value for this product (cat. A/e): 400 g/l VOC. This product contains max. 400 g/l VOC.

DISPOSAL:

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

COLOUR TONE:

2101 White Satin
2203 Light Ochre Satin
2204 Ivory Satin
2205 Sunflower Yellow Satin
2308 Nordic Red Satin
2310 Cedar/Redwood Satin
2311 Signal Red Satin
2404 Fir Green Satin
2501 Labrador Blue Satin
2506 Royal Blue Satin
2507 Dove Blue Satin
2606 Medium Brown Satin
2607 Dark Brown Satin
2703 Charcoal Satin
2704 Dusk Grey Satin
2708 Pebble Grey Satin
2716 Anthracite Grey Satin

PRODUCT INFORMATION

COUNTRY COLOUR

2735 Light Grey (RAL 7035) Satin
2742 Traffic Grey A (RAL 7042) Satin

SIZE:

0.75 l; 2.5 l; 5.0 l; 25 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if

provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information. For information specific to a certain country or region, please consult your local wholesaler or dealer:
OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26