


PRODUCT INFORMATION

WOOD FILLER

PERFECT FOR FILLING SMALL CRACKS AND JOINTS IN WOOD!



7300 White



7301 Beech




7302 spruce



7303 Mahogany



7304 Oak



7305 Creme White



7306 Black



PRODUCT DESCRIPTION:

Osmo Wood Filler is a ready-to-use pasty wood filler for patching small holes, cracks and joints in wood and engineered wood.

RECOMMENDED USE:

Osmo Wood Filler is suitable for patching small cracks, holes and joints in wood and engineered wood products. All colours can be mixed with each other. After drying, the surface can be recoated with all Osmo wood coatings.

TECHNICAL DATA:

Specific weight: 1.88-1.98 g/cm³ (DIN ISO 2811-2)

Viscosity: pasty

Odour: faint/mild, odourless after drying

pH value: 7-8

STORAGE:

5 years or longer if stored in the originally closed container. Do not expose to frost or temperatures above 30 °C!

SURFACE PREPARATION:

Clean any joints or holes in the wood, blowing them out or brushing them out if necessary.

METHODS OF APPLICATION:

Press the Wood Filler into the holes to be filled, applying light pressure. Trowel in Wood Filler until the surface is slightly raised, as the product will shrink slightly as it dries.

Repeat the process if necessary. After drying completely, sand the surface so that the Wood Filler remains flush with the holes. Always wear a dust mask when sanding! Remove the sanding dust – the dried Wood Filler can be recoated with any Osmo coating.

CLEANING OF TOOLS:

With soap and water.

DRYING TIME:

Allow to dry for approx. 1-3 hours, depending on the filling quantity and filling height.

NOTE:

All colours can be mixed with each other. Sand the wood filler with the same sandpaper grit as used to sand the wood surface.

CAUTION:

Contains mixture of CIT and MIT (3:1) (preservatives). May produce an allergic reaction.

Always follow the information on the product label.

DISPOSAL:

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

PRODUCT INFORMATION

WOOD FILLER

COLOUR TONE:

7300 White
7301 Beech
7302 spruce
7303 Mahogany
7304 Oak
7305 Creme White
7306 Black

SIZE:

100 g

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee

the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information.

For information specific to a certain country or region, please consult your local wholesaler or dealer:

OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26